

This Page Is Inserted by IFW Operations  
and is not a part of the Official Record

## **BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning documents *will not* correct images,  
please do not report the images to the  
Image Problem Mailbox.**

## AMENDMENTS TO THE CLAIMS

---

1. (currently amended) A system for exchanging heat with a fluid, for heating the fluid comprising:

a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, comprising a heating element, adapted to heat the heat exchanger, and a storing element, adapted to be heated by the heating element, and further adapted to maintain the fluid at a heated fluid temperature, and to enable the fluid to be heated above the heated fluid temperature substantially rapidly to a fluid dispensing temperature;

a fluid inlet, for enabling the fluid to flow into the heat exchanger; and

a fluid outlet, for enabling the heated fluid to flow out of the heat exchanger.

2. Canceled.

3. (original) The system of claim 1, wherein the heat exchanger is comprised of aluminum.

4. (original) The system of claim 1, further comprising a sealing element for sealing the heat exchanger.

5. (original) The system of claim 1, wherein the fluid inlet comprises an inlet valve.

6. (original) The system of claim 1, wherein the fluid outlet comprises an outlet valve.

7. (original) The system of claim 1, further comprising a sensing element for sensing the temperature of the heat exchanger, and for controlling and stabilizing the temperature thereof.

8. (original) The system of claim 1, further comprising a system for dispensing the fluid, which includes the heat exchanger therein.

9. (currently amended) The system of claim 1, wherein the storing element ~~heat exchanger~~ is further adapted to retain heat, such that, upon turning off the fluid inlet after dispensing fluid, any fluid remaining in the heat exchanger evaporates through the fluid outlet responsive thereto.

10. (original) The system of claim 1, further comprising a flow-controlling element for controlling the flow of the fluid from the fluid outlet for dispensing thereof.

11. (original) The system of claim 1, further comprising an operation-controlling element for controlling the operation of the system.

12. (original) The system of claim 2, wherein the storing element is adapted to enable the fluid to be in direct contact therewith.

13. Canceled.

14. (original) The system of claim 2, wherein the heating element is generally m-shaped.

15. (original) The system of claim 2, wherein the heating element is adapted to be connected to a heating source.

16. (original) The system of claim 2, wherein the channel is generally spiral-shaped.

17. (original) The system of claim 8, wherein the heat exchanger is located generally in the upper portion of the fluid dispensing system.

18. (original) The system of claim 8, wherein the fluid dispensing system further includes an outlet for dispensing the heated fluid.

19. (original) The system of claim 10, wherein the flow-controlling element comprises a flowmeter.

20. (original) The system of claim 11, wherein the operation-controlling element comprises a processing element for processing the temperature of the heat exchanger.

21. (original) The system of claim 18, wherein the fluid dispensing outlet comprises a fluid spray head.

22. (original) The system of claim 20, wherein the processing element comprises a microprocessor.

23. (original) A system for exchanging heat with a fluid, for heating the fluid comprising:

a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein;

a fluid inlet, for enabling the fluid to flow into the heat exchanger; and

a fluid outlet, for enabling the heated fluid to flow out of the heat exchanger;

wherein the heat exchanger is further adapted to retain heat, such that, upon turning off the fluid inlet after dispensing fluid, any fluid remaining in the heat exchanger evaporates through the fluid outlet responsive thereto.

Rule 1.126  
38

25. <sup>24</sup>

(original) A system for exchanging heat with a fluid, for heating the fluid comprising:

a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, wherein the heat exchanger comprises a storing element for storing heat, and a heating element for heating the storing element, and the heating element is generally m-shaped;

a fluid inlet, for enabling the fluid to flow into the heat exchanger; and

a fluid outlet, for enabling the heated fluid to flow out of the heat exchanger.

~~26.~~ <sup>25</sup>

(original) A system for exchanging heat with a fluid, for heating the fluid, comprising:

a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, wherein the heat exchanger has a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, and the channel is generally spiral-shaped;

a fluid inlet, for enabling the fluid to flow into the heat exchanger; and

a fluid outlet, for enabling the heated fluid to flow out of the heat exchanger.

<sup>26</sup>  
27. (original) A system for exchanging heat with a fluid, for heating the fluid, comprising:

means for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein;

<sup>26</sup>  
a fluid inlet, for enabling the fluid to flow into the heat exchanging means;  
and

a fluid outlet, for enabling the heated fluid to flow out of the heat exchanging means.

<sup>27</sup>  
28. (original) The system of claim <sup>26</sup>27, wherein the heat exchanging means are further adapted to retain heat, such that, upon turning off the fluid inlet after dispensing fluid, any fluid remaining in the heat exchanging means evaporates through the fluid outlet responsive thereto.

<sup>28</sup>  
29. (original) The system of claim <sup>26</sup>27, wherein the heat exchanging means comprise a storing element for storing heating, and a heating element for heating the storing element, and the heating element is generally m-shaped.

<sup>29</sup>  
~~30.~~ (original) The system of claim <sup>24</sup>~~27~~, wherein the heat exchanging means have a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, and the channel is generally spiral-shaped.

<sup>20</sup>  
~~31.~~ (currently amended) A method of exchanging heat with a fluid, for heating the fluid, in a system which comprises a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, comprising a heating element, adapted to heat the heat exchanger, and a storing element, adapted to be heated by the heating element, and further adapted to maintain the fluid at a heated fluid temperature, and to enable the fluid element to be heated above the heated fluid temperature substantially rapidly to a fluid dispensing temperature, a fluid inlet, for enabling the fluid to flow into the heat exchanger, and a fluid outlet, for enabling the heated fluid to flow out of the heat exchanger, wherein the method comprises:

enabling fluid to flow through the fluid inlet into the heat exchanger;

exchanging heat with the fluid in the heat exchanger so as to heat the fluid and store heat energy; ~~and~~


enabling heated fluid to flow out of the heat exchanger and through the fluid outlet; and



storing fluid heated to the heated fluid temperature in the storing element so as to retain heat for a substantial period of time to maintain the fluid at the heated fluid temperature.

~~32.~~<sup>31</sup> Canceled.

~~33.~~<sup>32</sup> (original) The method of claim ~~31~~<sup>30</sup>, wherein the heat exchanger is comprised of aluminum, and wherein exchanging heat comprises exchanging heat with the fluid in the aluminum heat exchanging means.

 ~~34.~~<sup>33</sup> (original) The method of claim ~~31~~<sup>30</sup>, further comprising a sealing element for sealing the heat exchanger, further comprising sealing the heat exchanger.

~~35.~~<sup>34</sup> (original) The method of claim ~~31~~<sup>30</sup>, wherein the fluid inlet comprises an inlet valve, and wherein enabling fluid inlet flow comprises enabling the fluid to flow through the inlet valve.

~~36.~~<sup>35</sup> (original) The method of claim ~~31~~<sup>30</sup>, wherein the fluid outlet flow comprises an outlet valve, and wherein enabling fluid outlet flow comprises enabling the fluid to flow through the outlet valve.

~~37.~~<sup>36</sup> (original) The method of claim ~~31~~<sup>30</sup>, further comprising a sensing element for sensing the temperature of the heat exchanger and for controlling and stabilizing the temperature thereof, further comprising sensing the temperature of the heat exchanger

and controlling and stabilizing the temperature thereof.

<sup>37</sup>  
~~38.~~ (original) The method of claim ~~31~~<sup>30</sup>, further comprising a system for dispensing the fluid, which includes the heat exchanger therein, further comprising dispensing the fluid from the fluid dispensing system.

<sup>38</sup>  
~~39.~~ (currently amended) The method of claim ~~31~~<sup>32</sup>, wherein the storing element ~~heat-exchanger~~ is further adapted to retain heat, such that, upon turning off the fluid inlet after dispensing fluid, any fluid remaining in the heat exchanger evaporates through the fluid outlet responsive thereto, further comprising evaporating any fluid remaining in the heat exchanger, after dispensing fluid, responsive to the retained heat in the storing element ~~heat-exchanger~~.

<sup>39</sup>  
~~40.~~ (original) The method of claim ~~31~~<sup>30</sup>, further comprising a flow-controlling element for controlling the flow of the fluid from the fluid outlet for dispensing thereof, further comprising controlling the flow of the fluid from the fluid outlet for dispensing thereof.

<sup>40</sup>  
~~41.~~ (original) The method of claim ~~31~~<sup>32</sup>, further comprising an operation-controlling element for controlling the operation of the system, further comprising controlling the operation of the system.

<sup>41</sup>  
~~42.~~ (original) The method of claim ~~32~~<sup>31</sup>, wherein the storing element is adapted to enable the fluid to be in direct contact therewith, and wherein exchanging heat

comprises enabling fluid to be in direct contact with the storing element.

~~43.~~<sup>42</sup> Canceled.

~~44.~~<sup>43</sup> (original) The method of claim ~~32~~<sup>31</sup>, wherein the heating element is generally m-shaped, and wherein exchanging heat further comprises heating the storing element through the generally m-shaped heating element.

~~45.~~<sup>44</sup> (original) The method of claim ~~32~~<sup>31</sup>, wherein the heating element is adapted to be connected to a power source, and wherein exchanging heat further comprises heating the heating element upon actuating the power source.

~~46.~~<sup>45</sup> (original) The method of claim ~~33~~<sup>32</sup>, wherein the channel is generally spiral-shaped, and wherein exchanging heat further comprises enabling fluid to flow into the generally spiral-shaped channel.

~~47.~~<sup>46</sup> (original) The method of claim ~~38~~<sup>37</sup>, wherein the heat exchanger is located generally in the upper portion of the fluid dispensing system, and wherein exchanging heat further comprises exchanging heat in the generally upper portion of the fluid dispensing system.

~~48.~~<sup>47</sup> (original) The method of claim ~~38~~<sup>37</sup>, wherein the fluid dispensing system further includes an outlet for dispensing the heated fluid, and wherein dispensing further comprises dispensing the fluid from the heated fluid dispensing outlet.

<sup>43</sup>  
~~49~~. (original) The method of claim <sup>79</sup>~~40~~, wherein the flow-controlling element comprises a flowmeter, and wherein controlling further comprises controlling the flow of the fluid in the flowmeter.

<sup>47</sup>  
~~50~~. (original) The method of claim <sup>46</sup>~~41~~, wherein the operation-controlling element comprises a processing element for processing the temperature of the heat exchanger, and wherein operation-controlling further comprises processing the temperature of the heat exchanger.

<sup>50</sup>  
~~51~~. (original) The method of claim <sup>46</sup>~~47~~, wherein the fluid dispensing outlet comprises a fluid spray head, and wherein dispensing further comprises dispensing through the fluid spray head.

<sup>51</sup>  
~~52~~. (original) The method of claim <sup>49</sup>~~50~~, wherein the processing element comprises a microprocessor, and wherein sensing further comprises processing through a microprocessor.

<sup>52</sup>  
~~53~~. (original) A method of exchanging heat with a fluid, for heating the fluid, in a system which comprises a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, a fluid inlet, for enabling the fluid to flow into the heat exchanger, and a fluid outlet, for enabling the

heated fluid to flow out of the heat exchanger, wherein the heat exchanger is further adapted to retain heat, such that, upon turning off the fluid inlet, after dispensing fluid, any fluid remaining in the heat exchanger evaporates through the fluid outlet responsive thereto, and wherein the method comprises:

enabling fluid to flow through the fluid inlet into the heat exchanger;

exchanging heat with the fluid in the heat exchanger so as to heat the fluid and store heat energy;

enabling heated fluid to flow out of the heat exchanger and through the fluid outlet;

turning off the fluid inlet;

dispensing fluid; and

evaporating any fluid remaining in the heat exchanger through the fluid outlet, responsive to the retained heat in the heat exchanger.

53

54. (original) A method of exchanging heat with a fluid, for heating the fluid, in a system which comprises a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, wherein the heat exchanger comprises a storing element for storing heat, and a heating element for heating the storing element, which is generally m-shaped, a fluid inlet, for enabling the fluid to flow into the heat exchanger, and a fluid outlet, for enabling the heated fluid to

flow out of the heat exchanger, wherein the method comprises:

enabling fluid to flow through the fluid inlet into the heat exchanger;

exchanging heat with the fluid through the generally m-shaped heating element in the heat exchanger, so as to heat the fluid and store heat energy; and

enabling heated fluid to flow out of the heat exchanger and through the fluid outlet.

<sup>54</sup>  
~~55.~~ (original) A method of exchanging heat with a fluid, for heating the fluid,


in a system which comprises a heat exchanger, for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, wherein the channel is generally spiral-shaped, a fluid inlet, for enabling the fluid to flow into the heat exchanger, and a fluid outlet, for enabling the heated fluid to flow out of the heat exchanger, wherein the method comprises:

enabling fluid to flow through the fluid inlet into the generally spiral-shaped channel in the heat exchanger;

exchanging heat with the fluid in the generally spiral channel in the heat exchanger so as to heat the fluid and store heat energy; and

enabling heated fluid to flow out of the generally spiral-shaped channel in the heat exchanger and through the fluid outlet.

<sup>55</sup>  
~~56~~. (original) A method of exchanging heat with a fluid, for heating the fluid, in a system which comprises means for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, a fluid inlet, for enabling the fluid to flow into the heat exchanging means, and a fluid outlet, for enabling the heated fluid to flow out of the heat exchanging means, wherein the method comprises:

 enabling fluid to flow through the fluid inlet into the heat exchanging means;

exchanging heat with the fluid in the heat exchanging means so as to heat the fluid and store heat energy; and

enabling heated fluid to flow out of the heat exchanging means and through the fluid outlet.

<sup>56</sup>  
<sup>55</sup>  
~~57~~. (original) The method of claim ~~56~~, wherein the heat exchanger is further adapted to retain heat, such that, upon turning off the fluid inlet after dispensing fluid, any fluid remaining in the heat exchanging means evaporates through the fluid outlet responsive thereto, further comprising evaporating any fluid remaining in the heat exchanging means, after dispensing of the fluid, responsive to the retained heat in the heat exchanging means.

<sup>57</sup>  
~~58.~~ (original) The method of claim ~~56~~<sup>55</sup>, wherein the heat exchanging means comprise means for storing heat, and means for heating the storing means, and the heating means are generally m-shaped, and wherein exchanging heat comprises heating the storing means through the generally m-shaped heating means and storing heat in the storing means.

<sup>58</sup>  
~~59.~~ (currently amended) The method of claim ~~56~~<sup>55</sup>, wherein the heat exchanging means have a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, and the channel is generally spirals~~spiral~~-shaped, and wherein exchanging heat comprises enabling fluid to flow into the generally spiral-shaped channel in the heat exchanging means and enabling fluid to be retained in the heat exchanging means.

<sup>59</sup>  
~~60.~~ (new) The system of claim 4, wherein the sealing element comprises a pair of plates, in which each plate is relatively thin, and the storing element is located between the pair of sealing element plates, and comprises a storing element plate which is relatively thick, wherein the thickness of the storing element plate is substantially greater than the thickness of each relatively thin sealing element plate, such that the storing element plate is adapted to retain heat for a substantial period of time to maintain the fluid at the heated fluid temperature.

<sup>60</sup>  
~~61.~~ (new) The method of claim ~~34~~<sup>33</sup>, wherein the sealing element comprises a pair of plates, in which each plate is relatively thin, and the storing element is



located between the pair of sealing element plates, and comprises a storing element plate which is relatively thick, wherein the thickness of the storing element plate is substantially greater than the thickness of each relatively thin sealing element plate, such that the storing element plate is adapted to retain heat for a substantial period of time to maintain the fluid at the heated fluid temperature, and wherein storing further comprises storing fluid heated to the heated fluid temperature in the relatively thick storing element plate so as to retain heat for a substantial period of time to maintain the fluid at the heated fluid temperature.

62. <sup>62.1</sup> (new) A system for exchanging heat with a fluid, for heating the fluid comprising:

heat exchanging means for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, comprising heating means for heating the heat exchanger, and storing means, adapted to be heated by the heating means, and further adapted to maintain the fluid at a heated fluid temperature, and to enable the fluid to be heated above the heated fluid temperature substantially rapidly to a fluid dispensing temperature;

fluid inlet means for enabling the fluid to flow into the heat exchanger; and

fluid outlet means for enabling the heated fluid to flow out of the heat exchanging means.

63. <sup>62</sup>

(new) A method of exchanging heat with a fluid, for heating the fluid, in a system which comprises heat exchanging means for exchanging heat with a fluid so as to heat the fluid, adapted to store heat energy, and to enable heat energy to be exchanged with the fluid to heat the fluid, having a channel therein adapted to enable the fluid to flow thereinto and therefrom, and to enable the fluid to be retained therein, comprising heating means, for heating the heating exchanger, and storing means, adapted to be heated by the heating means, and further adapted to maintain the fluid at a heated fluid temperature, and to enable the fluid to be heated above the heated fluid temperature substantially rapidly to a fluid dispensing temperature, fluid inlet means, for enabling the fluid to flow into the heat exchanger, and fluid outlet means, for enabling the heated fluid to flow out of the heat exchanger, wherein the method comprises:

enabling fluid to flow through the fluid inlet means into the heat exchanging means;

exchanging heat with the fluid in the heat exchanging means so as to heat the fluid and store heat energy;

enabling heated fluid to flow out of the heat exchanging means and through the fluid outlet means; and

storing fluid heated to the heated fluid temperature in the thick storing means so as to retain heat for a substantial period of time to maintain the fluid at the heated fluid temperature.